

PROJECT NUMBER

323666.03.17.07

BORING ID:

17C084

Sheet 1 of 2

## **SOIL BORING LOG**

PROJECT: Beale AFB-Site 17 PRB, Phase 1 Drilling LOCATION:

ELEVATION: 148.76 NORTHING: 2162225.72 EASTING: 6743591.33 DRILLING CONTRACTOR: Resonant Sonic International, Woodland, CA

ELEVATION: 148.76 NORTHING: 2162225.72 EASTING: 6743591.33 DRILLING CONTRACTOR: Resonant Sonic International, Woodland, CA						
DRILLING METHOD AND EQUIPMENT USED: Power Probe 9630 Direct Push						
WATER LEVELS: 14.5 ftt bgs					START: 8/17/2005 10:30:00 AM END:	LOGGER: B. Moayyad
DEPTH	DEPTH BGS (ft) STANDAR				CORE DESCRIPTION:	COMMENTS:
	INTERVAL (ft)			PENETRATION TEST RESULTS	SOIL NAME (USCS GROUP SYMBOL), COLOR, MOISTURE CONTENT, RELATIVE DENSITY, DRILLING FLUID LOSS,	DEPTH OF CASING, DRILLING RATE.
	RECOVERY		DRILLING FLUID LOSS,			
			TYPE-#	( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( (	OR CONSISTENCY, SOIL STRUCTURE,	TESTS, AND INSTRUMENTATION.
			SS=Split Spoon ST=ShelbyTube	6-6-6 (in) (N)	MINERALOGY.	
0 -	0-5	2.4/	ST=ShelbyTube	٧٠٠/	SM - SILTY SAND (SM) brown (7.5YR 4/3), moist, medium density,	
	-	4.0'				
					- ~75% fine sand, ~25% silt fines	
1-					<del>-</del>  -	
2 -					  -	_
					-	
3 -					-	_
					-	
4 -		2.5/ 4.0'			<del>-</del>	_
		7.0			-	
5 -	5-9				SW - WELL GRADED SAND WITH SILT AND GRAVEL (SW), brown	_
					(7.5YR	
6 =					- 4/4), moist, loose, ~15% subangular gravel, ~5-15% silt	
"-					-	
7 -					-	_
					-	
8 -	8-8	2.5/			SW-	_
		4.0'			_	
9 _	9-11.5				SW - WELL GRADED SAND WITH GRAVEL (SW), brown (7.5YR 4/4),	PID = 0.0 (soil), BZ = 0.0
					- saturated, loose to medium, ~15% subrounded gravel, ~75%	
10 -		1.2/			SW - fines	_
		2.0'			_	
11 -					-	_
	11.5-19				GC - CLAYEY GRAVEL (GC), brown (7.5YR 4/3), wet, medium to hard,	PID = 0.0
12 -		1.3/			- ~40% fine to coarse angular gravel, ~25% fine to coarse	_
		2.0'			- sand, ~35% silt and clay	
13 -					-	
"					-	
14 -		1.4/			GC -	_
		2.0				
15 -					( <del>-</del>   <u>-</u>	
.5 -					-	
16 -		0/2.0'			GC -	_
					-	
17 -					- 	_
10		מ מי			GC -	
18 -		0/2.0'			GC -	
19 -	19-22.5				GC - No recovery, likely same as above	PID = 0.0
					-	
20 -		0/2.0'			(-	_
					-	
21 -					( <del>-</del>	_
22 -		0/2.0'			( <del>-</del>	
		JI Z. U				



PROJECT NUMBER

323666.03.17.07

BORING ID:

17C084

Sheet 2 of 2

## **SOIL BORING LOG**

PROJECT: Beale AFB-Site 17 PRB, Phase 1 Drilling LOCATION: NORTHING: 2162225.72 ELEVATION: 148.76 EASTING: 6743591.33 DRILLING CONTRACTOR: Resonant Sonic International, Woodland, CA DRILLING METHOD AND EQUIPMENT USED: Power Probe 9630 Direct Push START: 8/17/2005 10:30:00 AM END: WATER LEVELS: 14.5 ftt bgs LOGGER: B. Moayyad DEPTH BGS (ft) STANDARD PENETRATION CORE DESCRIPTION: COMMENTS: INTERVAL (ft) DEPTH OF CASING, DRILLING RATE, SOIL NAME (USCS GROUP SYMBOL), COLOR, TEST RESULTS MOISTURE CONTENT, RELATIVE DENSITY, RECOVERY DRILLING FLUID LOSS, OR CONSISTENCY, SOIL STRUCTURE, TESTS, AND INSTRUMENTATION. TYPE-# MINERALOGY. 6-6-6 (in) SS=Split Spoor 22.5-24 11:15 Collect groundwater sample 17C084HP20 at 0/2.0' GC - No recovery, very hard 16-20 ft. Push is difficult 23 -GC - Refusal at 24 ft bgs 24 -25 -